

# DeltaCap - 3-phase PFC-Leistungskondensatoren; IP20

(MKD AC Technology, harzgefüllt - biologisch abbaubar)

50 Hz Leistung in kVAr	60 Hz Leistung in kVAr	Kapazität in µF 3 x	D * H mm Ø	Gewicht in kg	Type	Artikel Nr.	VPE (Stück)
<b>Rated voltage 230 V</b>							
0,5	0,6	10	50x150	0,4	MKD230-D-0.5	B32303A2002A530	50
0,7	0,8	14	50x150	0,4	MKD230-D-0.7	B32303A2002A730	50
1,0	1,2	20	50x150	0,4	MKD230-D-1.0	B32303A2012A030	50
1,5	1,8	30	63.5x150	0,6	MKD230-D-1.5	B32303A2012A530	12
2,0	2,4	40	63.5x150	0,6	MKD230-D-2.0	B32303A2022A030	12
2,5	3,0	50	63.5x150	0,8	MKD230-D-2.5	B32303A2022A530	12
5,0	6,0	100	75x200	1,1	MKD230-D-5.0	B32304A2052B030	6
7,5	9,0	151	75x275	1,4	MKD230-D-7.5	B32304A2072B530	6
10,0	12,0	201	85x275	1,7	MKD230-D-10.0	B32304A2102B030	4
12,5	15,0	251	85x350	2,2	MKD230-D-12.5	B32304A2122B530	4
15,0	18,0	301	85x350	2,2	MKD230-D-15.0	B32304A2152B030	4
<b>Rated voltage 400 V</b>							
1,0	1,2	7	50x150	0,4	MKD400-D-1.0	B32303A4012A000	50
1,5	1,8	10	50x150	0,4	MKD400-D-1.5	B32303A4012A500	50
2,0	2,4	13	50x150	0,4	MKD400-D-2.0	B32303A4022A000	50
2,5	3,0	17	50x150	0,4	MKD400-D-2.5	B32303A4022A500	12
5,0	6,0	33	63.5x150	0,6	MKD400-D-5.0	B32303A4052A000	12
6,3	7,6	42	75x163	0,8	MKD400-D-6.3	B32304A4071B500	6
7,5	9,0	50	75x163	0,9	MKD400-D-7.5	B32304A4072B500	6
8,3	10,0	55	75x200	1,1	MKD400-D-8.3	B32304A4101B000	6
10,0	12,0	67	75x200	1,1	MKD400-D-10.0	B32304A4102B000	6
12,5	15,0	83	75x275	1,4	MKD400-D-12.5	B32304A4122B500	4
15,0	18,0	100	75x275	1,4	MKD400-D-15.0	B32304A4152B000	4
16,7	20,0	111	85x275	1,8	MKD400-D-16.7	B32304A4201B000	4
20,0	24,0	133	85x275	1,8	MKD400-D-20.0	B32304A4202B000	4
25,0	30,0	166	85x350	2,2	MKD400-D-25.0	B32304A4252B000	4
30,0	--	199	96x275	2,4	MKD400-D-30.0	B32304A4302B000	4
<b>Rated voltage 415 V</b>							
1,0	1,2	6	50x150	0,4	MKD415-D-1.0	B32303A4012A010	50
1,5	1,8	9	50x150	0,4	MKD415-D-1.5	B32303A4012A510	50
2,0	2,4	12	50x150	0,4	MKD415-D-2.0	B32303A4022A010	50
2,5	3,0	15	63.5x150	0,6	MKD415-D-2.5	B32303A4022A510	12
5,0	6,0	31	63.5x150	0,8	MKD415-D-5.0	B32303A4052A010	12
6,3	7,6	39	75x200	1,0	MKD415-D-6.3	B32304A4071B510	6
7,5	9,0	46	75x200	1,1	MKD415-D-7.5	B32304A4072B510	6
10,0	12,0	62	75x275	1,4	MKD415-D-10.0	B32304A4102B010	6
12,5	15,0	77	75x275	1,4	MKD415-D-12.5	B32304A4122B510	6
15,0	18,0	92	85x275	1,7	MKD415-D-15.0	B32304A4152B010	4
20,0	24,0	123	85x350	2,2	MKD415-D-20.0	B32304A4202B010	4
20,8	25,0	128	85x350	2,4	MKD415-D-20.8	B32304A4251B010	4
25,0	30,0	154	85x350	2,4	MKD415-D-25.0	B32304A4252B010	4
30,0	--	185	96x350	2,7	MKD415-D-30.0	B32304A4302B010	4
<b>Rated voltage 440 V</b>							
0,9	1,1	5	50x127	0,4	MKD440-D-0.9	B32303A4011A040	50
1,0	1,2	6	50x127	0,4	MKD440-D-1.0	B32303A4012A040	50
1,2	1,4	7	50x127	0,4	MKD440-D-1.2	B32303A4011A540	50
1,5	1,8	9	50x127	0,4	MKD440-D-1.5	B32303A4012A540	50
2,0	2,4	11	50x150	0,5	MKD440-D-2.0	B32303A4020A040	50
2,1	2,5	12	50x150	0,5	MKD440-D-2.1	B32303A4021A540	50
2,5	3,0	14	63.5x150	0,7	MKD440-D-2.5	B32303A4022A540	12
4,2	5,0	23	63.5x150	0,7	MKD440-D-4.2	B32303A4051A040	12
5,0	6,0	27	63.5x150	0,8	MKD440-D-5.0	B32303A4052A040	12
6,3	7,6	35	75x163	0,8	MKD440-D-6.3	B32304A4071B540	6
7,5	9,0	41	75x200	1,1	MKD440-D-7.5	B32304A4072B540	6
8,3	10,0	46	75x200	1,1	MKD440-D-8.3	B32304A4101B040	6
10,0	12,0	55	75x275	1,4	MKD440-D-10.0	B32304A4102B040	6
10,4	12,5	57	75x275	1,4	MKD440-D-10.4	B32304A4121B540	6
12,5	15,0	69	75x275	1,4	MKD440-D-12.5	B32304A4151B040	6
15,0	18,0	82	85x275	1,7	MKD440-D-15.0	B32304A4152B040	4
16,7	20,0	92	85x275	1,7	MKD440-D-16.7	B32304A4201B040	4
20,0	24,0	110	85x350	2,2	MKD440-D-20.0	B32304A4202B040	4
20,8	25,0	114	85x350	2,2	MKD440-D-20.8	B32304A4251B040	4
25,0	30,0	137	85x350	2,2	MKD440-D-25.0	B32304A4252B040	4
28,0	33,6	154	85x350	2,2	MKD440-D-28.0	B32304A4282B040	4
30,0	--	164	85x350	2,7	MKD440-D-30.0	B32304A4302B040	4
33,0	--	181	85x350	2,7	MKD440-D-33.0	B32304A4332B040	4
33,8	--	185	85x350	2,7	MKD440-D-33.7	B32304A4332B840	4

## DeltaCap - 3-phase PFC-Leistungskondensatoren; IP20

(MKD AC Technology, harzgefüllt - biologisch abbaubar)

50 Hz Leistung in kVAr	60 Hz Leistung in kVAr	Kapazität in µF 3 x	D * H mm Ø	Gewicht in kg	Type	Artikel Nr.	VPE (Stück)
<b>Rated voltage 480 V</b>							
1,5	1,8	7	50x127	0,4	MKD480-D-1.5	B32303A4012A580	50
2,0	2,4	9	50x150	0,5	MKD480-D-2.0	B32303A4022A080	12
2,5	3,0	12	63.5x150	0,7	MKD480-D-2.5	B32303A4022A580	12
5,0	6,0	23	75x163	0,8	MKD480-D-5.0	B32304A4052B080	6
6,3	7,6	29	75x163	0,8	MKD480-D-6.3	B32304A4071B580	6
7,5	9,0	35	75x200	1,1	MKD480-D-7.5	B32304A4072B580	6
8,3	10,0	38	75x200	1,1	MKD480-D-8.3	B32304A4101B080	6
10,4	12,5	48	75x275	1,4	MKD480-D-10.4	B32304A4121B580	6
12,5	15,0	58	75x275	1,4	MKD480-D-12.5	B32304A4151B080	6
15,0	18,0	69	85x275	1,7	MKD480-D-15.0	B32304A4152B080	6
16,7	20,0	77	85x275	1,8	MKD480-D-16.7	B32304A4162B780	4
20,0	24,0	92	85x350	2,2	MKD480-D-20.0	B32304A4201B080	4
20,8	25,0	96	85x350	2,2	MKD480-D-20.8	B32304A4202B080	4
25,0	30,0	115	85x350	2,2	MKD480-D-25.0	B32304A4252B080	4
30,0	36,0	138	96x350	2,7	MKD480-D-30.0	B32304A4302B080	4
33,0	--	152	96x350	2,7	MKD480-D-33.0	B32304A4332B080	4

### Rated voltage 525 V

1,0	1,2	4	50x150	0,4	MKD525-D-1.0	B32303A5012A020	50
1,5	1,8	6	50x150	0,4	MKD525-D-1.5	B32303A5012A520	50
2,0	2,4	8	63.5x150	0,6	MKD525-D-2.0	B32303A5022A020	12
2,5	3,0	10	63.5x150	0,6	MKD525-D-2.5	B32303A5022A520	12
5,0	6,0	19	75x163	0,8	MKD525-D-5.0	B32304A5061B020	6
6,3	7,6	24	75x200	1,0	MKD525-D-6.3	B32304A5071B520	6
8,3	10,0	32	75x275	1,4	MKD525-D-8.3	B32304A5101B020	6
10,4	12,5	40	75x275	1,4	MKD525-D-10.4	B32304A5121B520	6
12,5	15,0	48	75x275	1,4	MKD525-D-12.5	B32304A5151B020	4
16,7	20,0	64	85x275	1,8	MKD525-D-16.7	B32304A5201B020	4
20,8	25,0	80	85x350	2,2	MKD525-D-20.8	B32304A5202B020	4
25,0	30,0	96	85x350	2,2	MKD525-D-25.0	B32304A5252B020	4
30,0	36,0	115	96x350	2,7	MKD525-D-30.0	B32304A5302B020	4
40,0	48,0	150	136x255	4,2	MKD525-D-40.0	B32304A5402B025	4