

PhaseCap Premium - 3-phase PFC-Leistungskondensatoren, IP20

MKK AC Technology, gasgefüllt

50 Hz Leistung in kVAr	60 Hz Leistung in kVAr	Kapazität in µF 3 x	D * H mm Ø	Gewicht in kg	Type	Artikel Nr.	VPE (Stück)
Rated voltage 230 V							
5,0	6,0	100	116x164	1,3	MKK230-D-5.0-01	B25667C3297A375	4
7,5	9,0	150	116x164	1,3	MKK230-D-7.5-01	B25667C2457A375	4
10,4	12,5	209	116x164	1,5	MKK230-D-10.4-01	B25667C2627A375	4
12,5	15,0	251	116x200	1,7	MKK230-D-12.5-01	B25667C2757A375	4
Rated voltage 400 V							
5,0	6,0	32	116x164	1,1	MKK400-D-5.0-01	B25667C5966A375	4
7,5	9,0	50	116x164	1,2	MKK400-D-7.5-01	B25667C3147A375	4
10,0	12,0	64	116x164	1,2	MKK400-D-10.0-01	B25667C4197A375	4
12,5	15,0	83	116x164	1,1	MKK400-D-12.5-01	B25667C3247A375	4
15,0	18,0	100	116x164	1,3	MKK400-D-15.0-01	B25667C3297A375	4
20,0	24,0	132	116x164	1,5	MKK400-D-20.0-01	B25667C3397A375	4
25,0	--	166	116x200	1,8	MKK400-D-25.0-01	B25667C3497A375	4
Rated voltage 415 V							
5,0	6,0	32	116x164	1,1	MKK415-D-5.0-01	B25667C5966A375	4
6,2	7,4	38	116x164	1,2	MKK415-D-6.2-01	B25667C5127A375	4
10,4	12,5	64	116x164	1,2	MKK415-D-10.0-01	B25667C4197A375	4
12,5	15,0	77	116x164	1,3	MKK415-D-12.5-01	B25667C4237A375	4
15,0	18,0	93	116x164	1,4	MKK415-D-15.0-01	B25667C4287A375	4
16,7	20,0	103	116x164	1,5	MKK415-D-16.7-01	B25667C4307A375	4
20,8	25,0	128	116x200	1,7	MKK415-D-20.0-01	B25667C4387A375	4
25,0	--	154	136x200	2,1	MKK415-D-25.0-01	B25667C4467A375	4
Rated voltage 440 V							
5,0	6,0	27	116x164	1,2	MKK440-D-5.0-01	B25667C4826A375	4
7,5	9,0	41	116x164	1,2	MKK440-D-7.5-01	B25667C4127A375	4
10,4	12,5	57	116x164	1,3	MKK440-D-10.4-01	B25667C4177A375	4
12,5	15,0	69	116x164	1,4	MKK440-D-12.5-01	B25667C4207A375	4
14,2	17,0	77	116x164	1,3	MKK440-D-14.2-01	B25667C4237A375	4
15,0	18,0	83	116x164	1,4	MKK440-D-15.0-01	B25667C4247A375	4
16,7	20,0	92	116x200	1,8	MKK440-D-16.7-01	B25667C4277A375	4
18,8	22,6	103	116x164	1,5	MKK440-D-18.8-01	B25667C4307A375	4
20,0	24,0	111	116x200	1,7	MKK440-D-20.0-01	B25667C4337A375	4
25,0	30,0	137	136x200	2,0	MKK440-D-25.0-01	B25667C4417A375	4
28,1	--	154	136x200	2,1	MKK440-D-28.1-01	B25667C4467A375	4
30,0	--	164	136x200	2,4	MKK440-D-30.0-01	B25667C4497A375	4
33,0	--	181	136x200	2,5	MKK440-D-33.0-01	B25667C4547A375	4
Rated voltage 480 V							
6,3	7,5	29	116x164	1,2	MKK480-D-6.25-01	B25667C4866A375	4
8,3	10,0	39	116x164	1,2	MKK480-D-8.3-01	B25667C5127A375	4
10,4	12,5	48	116x164	1,3	MKK480-D-10.4-01	B25667C5147A375	4
12,5	15,0	58	116x164	1,5	MKK480-D-12.5-01	B25667C5177A375	4
15,0	18,0	69	116x164	1,4	MKK480-D-15.0-01	B25667C4207A375	4
16,7	20,0	77	116x200	1,8	MKK480-D-16.7-01	B25667C5237A375	4
20,0	24,0	92	116x200	1,8	MKK480-D-20.0-01	B25667C4277A375	4
25,0	30,0	115	136x200	2,2	MKK480-D-25.0-01	B25667C4347A375	4
30,0	--	138	136x200	2,4	MKK480-D-30.0-01	B25667C4417A365	4
Rated voltage 525 V							
8,3	10,0	32	116x164	1,1	MKK525-D-8.3-01	B25667C5966A375	4
10,0	12,0	39	116x164	1,2	MKK525-D-10.0-01	B25667C5127A375	4
12,5	15,0	48	116x164	1,3	MKK525-D-12.5-01	B25667C5147A375	4
15,0	18,0	58	116x164	1,5	MKK525-D-15.0-01	B25667C5177A375	4
16,7	20,0	64	116x164	1,6	MKK525-D-16.7-01	B25667C5197A375	4
20,0	24,0	77	116x200	1,8	MKK525-D-20.0-01	B25667C5237A375	4
25,0	--	96	136x200	2,3	MKK525-D-25.0-01	B25667C5287A375	4
30,0	--	115	136x200	2,4	MKK525-D-30.0-01	B25667C5347A375	4

PhaseCap Premium - 3-phase PFC-Leistungskondensatoren, IP20

MKK AC Technology, gasgefüllt

50 Hz Leistung in kVAr	60 Hz Leistung in kVAr	Kapazität in µF 3 x	D * H mm Ø	Gewicht in kg	Type	Artikel Nr.	VPE (Stück)
------------------------------	------------------------------	---------------------------	---------------	------------------	------	-------------	----------------

Rated voltage 570 V

27,5	33,0	90	136x200	2,5	MKK570-D-27.5-01	B25667C5277A375	4
------	------	----	---------	-----	------------------	-----------------	---

Rated voltage 690 V

5,0	6,0	11	116x164	1,3	MKK690-D-5.0-01	B25667C6336A375	4
7,5	9,0	17	116x164	1,3	MKK690-D-7.5-01	B25667C6506A375	4
10,0	12,0	23	116x164	1,5	MKK690-D-10.0-01	B25667C6676A375	4
12,5	15,0	28	116x164	1,4	MKK690-D-12.5-01	B25667C6836A375	4
15,0	18,0	34	116x164	1,5	MKK690-D-15.0-01	B25667C6107A375	4
20,8	25,0	47	136x200	2,0	MKK690-D-20.8-01	B25667C6137A375	4
25,0	30,0	56	136x200	2,2	MKK690-D-25.0-01	B25667C6167A375	4

Rated voltage 765 V

30,0	36,0	55	136x200	2,4	MKK765-D-30.0-01	B25667C7167A375	4
------	------	----	---------	-----	------------------	-----------------	---

Rated voltage 800 V

5,0	6,0	8	116x164	1,2	MKK800-D-5.0-01	B25667C7246A375	4
7,5	9,0	12	116x164	1,2	MKK800-D-7.5-01	B25667C7376A375	4
10,0	12,0	17	116x164	1,3	MKK800-D-10.0-01	B25667C7496A375	4
12,5	15,0	21	116x164	1,4	MKK800-D-12.5-01	B25667C7626A375	4
15,0	18,0	25	116x164	1,5	MKK800-D-15.0-01	B25667C7746A375	4
20,0	24,0	33	136x200	2,0	MKK800-D-20.0-01	B25667C7996A375	4
25,0	30,0	41	136x200	2,3	MKK800-D-25.0-01	B25667C7127A375	4
28,0	33,0	46	136x200	2,4	MKK800-D-28.0-01	B25667C7137A375	4