

PhiCap - 3-phase PFC-Leistungskondensatoren, IP20

(MKP AC Technology, Harzgefüllt - biologisch abbaubar)

50 Hz Leistung in kVAr	60 Hz Leistung in kVAr	Kapazität in µF 3 x	D * H mm Ø	Gewicht in kg	Type	Artikel Nr.	VPE (Stück)
Rated voltage 230 V							
0,5	0,6	10	53x114	0,3	MKP230-D-0.5	B32343C2002A530	12
0,7	0,9	15	53x114	0,3	MKP230-D-0.7	B32343C2002A730	12
1,0	1,2	20	63.5x129	0,3	MKP230-D-1.0	B32343C2012A030	12
1,5	1,8	30	63.5x129	0,4	MKP230-D-1.5	B32343C2012A530	12
2,0	2,5	42	75x138	0,4	MKP230-D-2.0	B32344E2022A030	6
2,5	3,0	50	75x138	0,4	MKP230-D-2.5	B32344E2022A530	6
5,0	6,0	100	75x198	0,6	MKP230-D-5.0	B32344E2052A030	6
7,5	9,0	150	85x198	0,8	MKP230-D-7.5	B32344E2072A530	4
10,0	12,0	200	85x273	1,2	MKP230-D-10.0	B32344E2102A030	4
12,5	15,0	250	85x273	1,5	MKP230-D-12.5	B32344E2122A530	4
15,0	--	300	85x348	1,5	MKP230-D-15.0	B32344E2152A030	4
Rated voltage 400 V							
1,0	1,2	7	53x114	0,3	MKP400-D-1.0	B32343C4012A000	12
1,5	1,8	10	53x114	0,3	MKP400-D-1.5	B32343C4012A500	12
2,0	2,4	13	63.5x129	0,4	MKP400-D-2.0	B32343C4022A000	12
2,5	3,0	17	63.5x129	0,4	MKP400-D-2.5	B32343C4022A500	12
5,0	6,0	33	63.5x129	0,4	MKP400-D-5.0	B32343C4052A000	12
6,3	7,5	42	75x160	0,5	MKP400-D-6.3	B32344E4071A500	6
7,5	9,0	50	75x160	0,5	MKP400-D-7.5	B32344E4072A500	6
8,3	10,0	55	75x160	0,5	MKP400-D-8.3	B32344E4101A000	6
10,0	12,0	67	75x198	0,6	MKP400-D-10.0	B32344E4102A000	6
12,5	15,0	83	85x198	0,8	MKP400-D-12.5	B32344E4122A500	4
15,0	18,0	100	85x198	0,8	MKP400-D-15.0	B32344E4152A000	4
16,7	20,0	111	85x198	0,8	MKP400-D-16.7	B32344E4201A000	4
20,0	24,0	133	85x273	1,2	MKP400-D-20.0	B32344E4202A000	4
25,0	--	166	85x273	1,5	MKP400-D-25.0	B32344E4252A000	4
30,0	--	199	90x348	2,5	MKP400-D-30.0	B32344E4302A000	4
Rated voltage 415 V							
1,0	1,2	6	53x114	0,3	MKP415-D-1.0	B32343C4012A010	12
1,5	1,8	9	53x114	0,3	MKP415-D-1.5	B32343C4012A510	12
2,0	2,4	12	53x114	0,4	MKP415-D-2.0	B32343C4022A010	12
2,5	3,0	15	63.5x129	0,4	MKP415-D-2.5	B32343C4022A510	12
5,0	6,0	31	63.5x154	0,4	MKP415-D-5.0	B32343C4052A010	12
6,3	7,5	39	75x160	0,5	MKP415-D-6.3	B32344E4071A510	6
7,5	9,0	46	75x198	0,6	MKP415-D-7.5	B32344E4072A510	6
10,0	12,0	62	75x198	0,6	MKP415-D-10.0	B32344E4102A010	6
12,5	15,0	77	85x198	0,8	MKP415-D-12.5	B32344E4122A510	4
15,0	18,0	92	85x273	1,2	MKP415-D-15.0	B32344E4152A010	4
20,0	24,0	123	85x273	1,2	MKP415-D-20.0	B32344E4202A010	4
25,0	--	154	85x348	1,5	MKP415-D-25.0	B32344E4252A010	4
Rated voltage 440 V							
0,9	1,0	5	53x114	0,3	MKP440-D-0.9	B32343C4011A040	12
1,0	1,2	6	53x114	0,3	MKP440-D-1.0	B32343C4012A040	12
1,2	1,5	7	53x114	0,3	MKP440-D-1.2	B32343C4011A540	12
1,5	1,8	8	53x114	0,3	MKP440-D-1.5	B32343C4012A540	12
2,1	2,5	11	53x114	0,4	MKP440-D-2.1	B32343C4021A540	12
2,5	3,0	13	63.5x129	0,3	MKP440-D-2.5	B32343C4022A540	12
4,2	5,0	23	63.5x129	0,4	MKP440-D-4.2	B32343C4051A040	12
5,0	6,0	27	63.5x154	0,5	MKP440-D-5.0	B32343C4052A040	12
6,3	7,5	34	75x160	0,5	MKP440-D-6.3	B32344E4071A540	6
7,5	9,0	41	75x160	0,5	MKP440-D-7.5	B32344E4072A540	6
8,3	10,0	46	75x198	0,6	MKP440-D-8.3	B32344E4101A040	6
10,0	12,0	55	75x198	0,6	MKP440-D-10.0	B32344E4102A040	6
10,4	12,5	57	75x198	0,6	MKP440-D-10.4	B32344E4121A540	6
12,5	15,0	69	85x198	0,8	MKP440-D-12.5	B32344E4151A040	4
15,0	18,0	82	85x273	1,1	MKP440-D-15.0	B32344E4152A040	4
16,7	20,0	92	85x273	1,2	MKP440-D-16.7	B32344E4201A040	4
20,8	25,0	114	85x273	1,2	MKP440-D-20.8	B32344E4251A040	4
25,0	30,0	138	85x348	1,5	MKP440-D-25.0	B32344E4252A040	4
28,0	--	154	85x348	1,5	MKP440-D-28.0	B32344E4282A040	4
30,0	--	165	85x348	1,6	MKP440-D-30.0	B32344E4302A040	4

PhiCap - 3-phase PFC-Leistungskondensatoren, IP20

(MKP AC Technology, Harzgefüllt - biologisch abbaubar)

50 Hz Leistung in kVAr	60 Hz Leistung in kVAr	Kapazität in µF 3 x	D * H mm Ø	Gewicht in kg	Type	Artikel Nr.	VPE (Stück)
------------------------------	------------------------------	---------------------------	---------------	------------------	------	-------------	----------------

Rated voltage 480 V

1,5	1,8	7	63.5x129	0,4	MKP480-D-1.5	B32343C4012A580	12
2,0	2,4	9	63.5x129	0,4	MKP480-D-2.0	B32343C4022A080	12
2,5	3,0	11	63.5x129	0,4	MKP480-D-2.5	B32343C4022A580	12
4,2	5,0	19	63.5x154	0,5	MKP480-D-4.2	B32343C4051A080	12
4,2	5,0	19	75x160	0,5	MKP480-D-4.2	B32344E4051A080	6
5,0	6,0	23	75x160	0,5	MKP480-D-5.0	B32344E4052A080	6
6,3	7,6	29	75x160	0,5	MKP480-D-6.3	B32344E4071A580	6
7,5	9,1	35	75x198	0,6	MKP480-D-7.5	B32344E4072A580	6
8,4	9,9	38	75x198	0,6	MKP480-D-8.3	B32344E4101A080	6
10,4	12,5	48	85x198	0,8	MKP480-D-10.4	B32344E4121A580	4
12,5	15,1	58	85x198	0,8	MKP480-D-12.5	B32344E4151A080	4
15,0	18,0	69	85x273	1,2	MKP480-D-15.0	B32344E4152A080	4
16,7	20,1	77	85x273	1,2	MKP480-D-16.7	B32344E4162A780	4
20,8	25,1	96	85x273	1,5	MKP480-D-20.8	B32344E4202A080	4
25,0	30,0	115	85x348	1,5	MKP480-D-25.0	B32344E4252A080	4
30,0	36,1	138	90x348	1,5	MKP480-D-30.0	B32344E4302A080	4

Rated voltage 525 V

1,0	1,2	4	53x114	0,3	MKP525-D-1.0	B32343C5012A020	12
1,5	1,8	6	53x114	0,3	MKP525-D-1.5	B32343C5012A520	12
2,0	2,4	8	63.5x129	0,4	MKP525-D-2.0	B32343C5022A020	12
2,5	2,7	9	63.5x129	0,4	MKP525-D-2.5	B32343C5022A520	12
5,0	6,0	19	75x160	0,3	MKP525-D-5.0	B32344E5061A020	6
6,3	7,6	24	75x160	0,5	MKP525-D-6.3	B32344E5071A520	6
8,3	10,0	32	75x198	0,6	MKP525-D-8.3	B32344E5101A020	6
10,4	12,5	40	85x198	0,8	MKP525-D-10.4	B32344E5121A520	4
12,5	15,0	48	85x273	1,1	MKP525-D-12.5	B32344E5151A020	4
16,7	20,0	64	85x273	1,2	MKP525-D-16.7	B32344E5201A020	4
20,8	25,0	80	85x348	1,5	MKP525-D-20.0	B32344E5202A020	4
25,0	30,0	96	85x348	1,5	MKP525-D-25.0	B32344E5252A020	4